

### **Listing of Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-4 (canceled)

5. (currently amended) A hybridization apparatus of the type providing a chamber for containing a hybridization liquid over a hybridization material immobilized on a substrate comprising:

a substrate comprising a substantially flat top surface adapted to support an immobilized hybridizable material;

a cover slip comprising

- a thickness of at least substantially 1 mm,
- a substantially flat bottom surface, and
- two substantially parallel, opposed edges bounding the bottom surface,
- a pair of spacer segments attached to the bottom surface of the cover slip, each of the pair of spacer segments extending along substantially a full length of a different one of the opposed edges and forming a hybridization chamber between the spacer segments, the bottom surface of the cover slip and the top surface of the substrate, the hybridization chamber extending substantially to opposite ends of the cover slip, and the hybridization chamber adapted to contain the hybridization material **[[specimen]]** when the cover slip is placed on the substrate with the spacer segments sandwiched therebetween, **[[wherein]]** the cover slip **[[has a]]** thickness being sufficient to provide a cover slip beam stiffness that prevents adhesion forces ~~created by the introduction of hybridization liquid into the hybridization chamber~~ from substantially changing a substantially constant distance between the bottom surface of the cover slip and the top surface of the **[[substance]]** substrate, the adhesion forces being created by the introduction of hybridization liquid into the hybridization chamber.

Claims 6-43 (canceled)

44. (currently amended) A hybridization apparatus as in claim 5 wherein the cover slip is ~~made of flat glass having~~ comprises a thickness greater than 1 mm and less than or equal to 2.0 mm.

45. (previously presented) A hybridization apparatus as in claim 5 wherein the cover slip has a flatness of about +/- 0.005 mm.

46. (previously presented) A hybridization apparatus as in claim 5 wherein each spacer segment is a thin bar having a width of about 75 mm.

47. (previously presented) A hybridization apparatus as in claim 5 wherein the spacer segments are printed on the bottom surface of the cover slip.

48. (previously presented) A hybridization apparatus as in claim 5 wherein the hybridizable material is arranged in a microarray.

49. (previously presented) A hybridization apparatus as in claim 5 wherein the hybridizable material comprises a nucleic acid.

50. (previously presented) A hybridization apparatus as in claim 5 wherein the hybridizable material comprises a protein.

51. (previously presented) A hybridization apparatus as in claim 5 wherein the hybridization liquid facilitates hybridization reactions between complementary nucleic acids.

52. (previously presented) A hybridization apparatus as in claim 5 wherein the hybridization liquid facilitates hybridization reactions between an antibody and antigen.

53. (previously presented) A hybridization apparatus as in claim 5 wherein the substrate and the cover slip are flat, rectangular glass members.

54. (previously presented) A hybridization apparatus as in claim 5 wherein the thickness of the spacer segments is substantially constant.

55. (previously presented) A hybridization apparatus as in claim 5 further comprising additional spacer segments along the periphery of the bottom surface of the cover slip.

56. (previously presented) A hybridization apparatus as in claim 5 further comprising additional spacer segments on the bottom surface of the cover slip and located between said longitudinal spacer segments.

57. (previously presented) A hybridization apparatus as recited in claim 5 wherein at least two channels are formed between the recited spacer segments for the introduction of hybridization fluid into the hybridization chamber and the venting thereof.